

PVC and TPO Clad Metal Sheets DATA SPECS

from Arvinyl



The Arvinyl Advantage

Arvinyl Laminates is a leading provider of PVC and TPO clad metal sheets to the roofing industry.

Through Arvinyl's proprietary lamination process, a highgrade PVC or TPO membrane is adhered to a high-quality metal substrate, which results in a premium roofing laminate with a high-level bond strength.

Typical Properties	
Metal Substrate	Galvanized Steel, Stainless Steel and Aluminum
Length	120 in. ± 0.250 (special length by request)
Width	48 in. ± 0.125
Weight	1.34 lb./ft. ²
Thickness	16-24 gauge
Packaging	25 or 50 sheets per pallet



Arvinyl's TPO color options

Testing Properties	
Specific Gravity - min. 1.20	ASTM D792
Tensile - min. 55	ASTM D882
Elongation % - min. 350	ASTM D882
100% Modulus (lbs.) - min. 25	ASTM D882
Ball Test	CS245-62
Impact Test	ASTM D6905
Boiling Water @ 1 hour	CS245-62

Call Today for a Quote!

1-800-ARVINYL **1-800-278-4695**

www.arvinyl.com/roofing/

ISO 9001:2015 Certification

Arvinyl Laminates received the ISO 9001:2015 certificate through Perry Johnson Registrars, Inc., based on a review of our quality management system.







Arvinyl Laminates

233 N. Sherman Avenue Corona, California 92882 Email: Sales@arvinyl.com URL: www.arvinyl.com/roofing/

Office: 951-371-7800